

# TECHNICAL DATA SHEET



Bouni® 7452  
Version 2.0 @CN

Reversion Date: 07/08/2020  
Print Date: 07/10/2020

## Chemical nature

Propylene maleic anhydride copolymers

## Benefits

- Promote adhesion to various substrates
- Effective dispersing agent of pigments and fillers
- Excellent anti-slip properties
- Good wetting of fiber

## Delivery Specifications/\*General Properties

Characteristics	Unit	Value	Test Method
*Drop Point	[°C]	153~160	GB/T 4507-2014
*Viscosity @170°C	[mPa·s]	800~1400	GB/T 2794-2013
Density	[g/cm <sup>3</sup> ]	0.94	GB/T 1033.2-2010
*Acid Number	[mgKOH/g]	40~46	GB/T 4945-2002
Grafting Rate	[%]	7	Titration
Appearance	-	Yellow Granule	-

## Packaging/Storage

Products are packaged in net weight 25 kg compound bags and shipped on pallets, 40 bags to a pallet. Please store in a dry area at normal ambient temperatures. Minimum shelf life is 2 years from the date of shipping when properly stored.

## Safety

The product does not require a hazard warning label.

For further information please refer to the Material Safety Data Sheet(MSDS).

## Contact

**www.bouni-wax.com**

DaRong Center, No.180 Haier Road, QingDao City, 266101

TEL: +86-532-55760890

FAX: +86-532-55760890

**Disclaimer:** The information submitted in this publication is based on our current knowledge and experience. In view of the many factors that may affect processing and application, these data do not relieve processors of the responsibility of carrying out their own tests and experiments; neither do they imply any legally binding assurance of suitability for a specific purpose. It is the responsibility of those to whom we supply our products to ensure that any proprietary rights and existing laws and legislation are observed.

**END OF TECHNICAL DATA SHEET**

® Registered trademark of Bouni.

© 2020 QingDao Bouni Chemical Co.,Ltd.